

**VALVOLA DI RITARDO AVVIAMENTO / EASY STARTER**  
**RETARDEUR DU DÉPART/ VÁLVULA DE RETRASO ARRANQUE**



CODICE CODE	ATTACCO CONNECTION	PORTAGOMMA HOSE BARB	PRESS. NOMINALE RATED PRESSURE	PRESSIONE MAX MAX PRESSURE	PORTATA FLOW RATE	TEMP. NOM. RATED TEMP.
86.1650.00.2	3/8 BSP - M	∅ 8 mm	250 bar 3600 Psi	280 bar 4000 Psi	30 l/min 8 GPM	80 °C 175 °F

**PRESSOSTATI PER TOTAL / PRESSURE SWITCHES FOR TOTAL STOP**  
**PRESSOSTATS POUR ARRÊT TOTAL / INTERRUPTORES DE PRESIÓN**



CODICE CODE	PRESS. DI INTERVENTO PRESSURE ON	MAX PRESSIONE MAX PRESSURE	MATERIALE MATERIALS	ATTACCO CONNECTION	Volt	ASSORB. MAX MAX. ABSORB.
82.5480.60.2	40 bar 580 PSI	250 bar 3600 PSI	OT BRASS	1/4 BSP-M	250	6 A
82.5480.70.2	40 bar 580 PSI	250 bar 3600 PSI	OT BRASS	1/4 BSP-M	250	16 A

**MANOMETRI / PRESSURE GAUGES**  
**MANOMETRES / MANÓMETROS**



CODICE CODE	DESCRIZIONE DESCRIPTION	ENTRATA INLET	SCALA SCALE
83.0096.20.2	DN 63 - ABS	1/4 BSP - M ATTACCO RADIALE	0 - 250 bar 0 - 3600 PSI
83.0096.50.2	DN 63 - INOX		0 - 250 bar 0 - 3600 PSI
83.0096.00.2	DN 63 - ABS	1/4 BSP -M RADIAL CONNECTION	0 - 315 bar 0 - 4568 PSI
83.0097.00.2	DN 63 - INOX		0-600 bar 0-8700 PSI



CODICE CODE	DESCRIZIONE DESCRIPTION	ENTRATA INLET	SCALA SCALE
83.0096.25.2	DN 63 - ABS	1/4 BSP - M ATTACCO POSTERIORE	0 - 250 bar 0 - 3600 PSI
83.0096.05.2	DN 63 - ABS		0 - 315 bar 0 - 4568 PSI
83.0097.50.2	DN 63 - INOX	1/4 BSP -M BACK CONNECTION	0-600 bar 0-8700 PSI