








customized highest state highest  
**PRECISION OF THE ART** **QUALITY**  
**VALVOLE SICUREZZA**  
**SAFETY VALVES - VANNES DE SECURITE - VÁLVULAS DE SEGURIDAD**



Temperatura max: 90°C - 195°F  
 Max temperature: 90°C - 195°F  
 Température max: 90°C - 195°F  
 Temperatura máx: 90°C - 195°F

	CODICE CODE	MODELLO MODEL	PRESSIONE MAX MAX PRESSURE		PORTATA FLOW		Attacco pompa Port size	Scarico By-pass	PESO WEIGHT	
			BAR	PSI	l/min	GPM			Kg	lbs
	86.1670.00.2	VS 250	250	3600	24	6.3	3/8 BSP - F	3/8 BSP - F	0.36	0.8
	86.1675.00.2	VS 250-2 BY-PASS 1/4	250	3600	24	6.3	N°2 3/8 BSP - F	1/4 BSP - F	0.46	1.0
	86.1660.00.2	VS 250-2 BY-PASS 3/8	250	3600	24	6.3	N°2 3/8 BSP - F	3/8 BSP - F	0.46	1.0
	86.1676.00.2	VS 350	350	5100	24	6.3	N°2 3/8 BSP - F	3/8 BSP - F	0.46	1.0
 ACCIAIO INOX STAINLESS STEEL	86.1677.00.2	VS 280 (AISI 303)	280	4000	80	21	N°2 1/2 BSP - F	1/2 BSP - F	1.21	2.7
	86.1678.00.2	VS 400 (AISI 303)	400	5800	80	21	N°2 1/2 BSP - F	1/2 BSP - F	1.21	2.7
	86.1679.00.2	VS 500	500	7250	80	21	1/2 BSP - F	1/2 BSP - F	1.42	3.1
	86.1779.00.2	VS 180	180	2610	200	53	3/4 BSP - F	1/2 BSP - F	0.82	1.8
	86.1680.00.2	VS 200	200	2900	450	119	1"1/4 BSP-F	1"1/4 BSP-F	3.8	8.4